


---

# Cavity wall & Ceiling Installation guide for Amina Edge Invisible loudspeakers

using BackboxCV345



*amina*®  
THE INVISIBLE SPEAKER CO.

---

# Amina Edge Fully Concealed Loudspeakers

The Amina Edge series of Loudspeakers are designed to deliver best in class audio performance in fully concealed in-wall and in-ceiling applications, preserving the interior aesthetic of any space.

Featuring a unique tapered perimeter, Amina Edge products are designed specifically for installation using a dry-wall / dry lining approach. The perimeter of the product is taped and joined. The front surface of the speaker is then decorated with paint, wallpaper or fabric.



# Contents

Caution: Read before installing this product .....	3	Finishing .....	22
Environmental.....	5	Filling the perimeter.....	22
Message from the Managing Director .....	6	Taping the joints.....	22
About the Manufacturer .....	6	Feathering the panel edge.....	23
Introduction .....	7	Finishing.....	23
Installation options.....	7	Decorating.....	24
Unpacking .....	7	Maintenance and cleaning.....	24
Packaging .....	7	Accessories.....	25
Compatibility .....	7	Subwoofers.....	25
Overview .....	8	Troubleshooting.....	26
Setup tips.....	9	Advice for testing .....	26
Installation.....	11	No or low sound output.....	26
Mounting accessories.....	11	Distortion, buzzing or rattles at modest volumes .....	27
Speaker protectors.....	12	Very low output after speaker passes electrical tests.....	27
Correct fixing method for BackboxCV	13	Distortion at higher volume levels.....	27
Shims .....	17	Specifications.....	28
Fixing shims to the speaker .....	17	Amina Edge series - Plaster up to products.....	28
Fixing shims to the BackboxCV.....	17	Warranty information.....	29
Alignment and preparation .....	18	Copyright information .....	29
Drywall / Dry line .....	18	Contact information.....	29
Alignment required for plastering .....	18		
Shim sizes .....	18		
Full wet skim coat .....	19		
Alignment required for plastering .....	19		
Retrofit / pre-skimmed plasterboard..	20		
Alignment required for plastering .....	20		
Shim sizes .....	20		
Testing the speakers .....	21		

---

## Caution: Read before installing this product

This manual contains detailed instructions required to install your Amina Edge Invisible Loudspeaker into a cavity wall using a BackboxCV housing.



### CAUTION:

The installation guide included with a BackboxCV describes the different installation steps required for other models of Amina Invisible loudspeakers. Refer only to the Installation steps in this guide when installing an Edge loudspeaker.



### WARNING:

No attempt should be made to install a BackboxCV within existing building structures unless you are certain that no electric cables, water pipes, gas pipes or supporting joists will be cut through.



### FIRE PROTECTION:

*When making an intrusion into an internal wall or ceiling to install an Amina loudspeaker be sure to check the appropriate regulations pertaining to the required fire rating. Depending on the location of the intrusion and the applicable regulations it may be necessary to build in or install additional fire rated components or products to surround the speaker and back box. Amina Technologies take no responsibility for the correct specification and installation of any such fire protection system that is required behind their loudspeakers.*

---

# Caution: Read before installing this product

## Please read carefully before installing this product

- To ensure correct installation, please read this guide carefully and keep in a safe place for future reference.
  - Install this product in a cool, dry, clean place - away from direct sunlight and heat sources, vibration, chemical fumes, dust and moisture (steam).
  - Do not expose this product to sudden temperature changes or locate it in an environment with high humidity. This is to prevent condensation forming inside which may cause damage to the product.
  - Do not clean this product with chemical solvents as this may cause damage to the finish. Use a clean, dry or damp cloth.
  - After installation, avoid pushing on the wall or ceiling surface immediately in front of the speaker. Excessive excursion, whilst unlikely to damage the speaker, will undoubtedly crack the plaster around its perimeter.
  - Do not attempt to modify or repair the product. Contact your distributor or Amina if a fault should occur.
  - The rear of the product should not be subject to chemical cleaning and should not be painted in any way.
  - Ensure that all installation mounting surfaces are able to support the weight of the BackboxCV with that of your chosen speaker.
  - You will require a minimum cavity depth of 75mm behind the plasterboard to allow the use of a BackboxCV.
-

---

## Environmental

- Before installing, ensure that the building is environmentally sealed, de-humidified (to a maximum of RH50%) and at a stable temperature of at least 16 degrees centigrade (61 degrees Fahrenheit)
  - This product should not be used with single thick coat plaster solutions or with other finishing methods that take days (rather than hours) to dry out.
  - Please be aware that when this product is fitted in simple (stud on rafter with plasterboard/floorboard attached on either side) stud walls or wooden rafter ceiling/floor structures vibrational energy is inevitably transferred into the building structure. This energy can travel for some considerable distance up, down and along the structure. It is therefore recommended the product be fitted within acoustically insulated stud walls or ceiling sections where possible. Special care should be taken when installing the product in multi occupancy buildings.
  - Completed installations and fully dried plaster surfaces should be finished with permeable coatings / materials to allow moisture in that coating or the adhesives used to apply those materials, to dry into the environment quickly.
-

---

## Message from the Managing Director

Congratulations and thank you for purchasing an Amina Technologies high performance invisible loudspeaker.

At Amina we are proud of being at the forefront of flat panel loudspeaker technology. All the components that make up your loudspeaker have been developed specifically to provide the ultimate in sound quality and reliability, whilst allowing you to decorate, furnish and enjoy your home in any way you wish without any visible 'clutter' from your audio system.

At the heart of an Amina loudspeaker is our high performance vibrational panel driver, featuring a unique high power neodymium magnet motor system. This enables the product to provide high quality, high loudness levels from such a compact design. Please take a moment to read this guide which will help you achieve the best possible performance from your product.

Thank you and enjoy listening.

Richard Newlove

MD - Amina Technologies Ltd

## About the Manufacturer

Amina Technologies Ltd is the world's leading designer and manufacturer of truly invisible loudspeaker solutions. Our invisible loudspeakers have been used in a wide range of both commercial and residential applications for over fifteen years.

Luxurious hotels & spas, exclusive retail outlets and stunning private residences have all benefitted from using Amina invisible loudspeakers, not only for its' incredible aesthetic quality, but for its' absolute ability to reproduce sensationally clear audio across any space. Amina has created the very best discrete audio solution for architects, interior designers and all design conscious clients.

See our website for more details about Amina and a selection of prestigious projects completed using our products.

## Introduction

Thank you for purchasing Amina Edge invisible loudspeakers. Properly installed, these loudspeakers will provide high quality sound for many years, even decades, to come.

### Installation options

Installation is simple, but should only be attempted by professional building trades with plastering experience and who have ideally completed an Amina installation training course.

Amina loudspeakers can not be mounted into a wall without the correct fixing accessories, supplied by Amina for each wall type.

Please read the instructions carefully, particularly the Installation section which contains important advice to select the correct wall-mounting accessories.

This manual should then be read in conjunction with the associated manual supplied with your mounting accessory.

## Unpacking

Unpack the unit.

Check that your carton contains the correct number of items - a single speaker, or two if ordered as a pair.

Retain this Installation Guide. If you pass the unit on to a third party make sure you pass on the Installation Guide.

## Packaging



### CAUTION:

Take care when removing the loudspeakers from the carton.

The packaging for Amina Edge loudspeakers has been carefully designed to protect the product during transit. Please retain it in the unlikely event you need to return the product to your dealer or to Amina. Please recycle the packaging should you wish to dispose of it.


The outer carton is made up of 80% recycled board.

## Compatibility

This installation guide only covers installation of the Amina Edge range of Invisible loudspeakers within a BackboxCV345.

If you are installing a BackboxCV with any other type of Amina Invisible loudspeaker, refer to the General Installation guide supplied with the BackboxCV that covers all other loudspeaker models.

# Overview



1. Electrical connection (to an amplifier, via APU)
2. High power neodymium magnet structures
3. Active panel surface
4. Aluminium chassis

---

# Setup tips

## APU protection

Amina loudspeakers must be used with an APU protection device or another protection device, approved by Amina. Please refer to the instructions supplied with the APU devices and full warranty information for further details.

## Installation Backboxes

Amina Edge loudspeakers have been designed for optimum sound quality when installed with the Amina BackboxCV345. We recommend that they are used wherever possible in a cavity type installation. If our basic fixing block kit is used you may find that the low/mid frequencies are reproduced less accurately, but any effect will be very much installation specific.

## Wall or Ceiling Placement

Amina loudspeakers are suitable for both wall and ceiling installations. When the most uniform audio coverage in a room is required, space the loudspeakers evenly in the ceiling. However, if the room has a height greater than 6m (19'), Amina suggests installing them in the walls at a height of around 1.8m (6').

In dedicated listening rooms where loudspeakers are used in stereo or multi channel systems, position them in the walls so that the centre point of the speaker is approximately 1 – 1.8m (3.5 - 6') from the floor. This will give excellent results, but don't worry, if this is not possible to achieve in your room, the audio characteristics of Amina loudspeakers make exact positioning according to stereo, 5.1 and 7.1 conventions far less critical.

## Audio Characteristics

Amina loudspeakers generate sound in a similar way to an acoustic musical instrument. The speaker's front face is effectively the "musical" soundboard and the sound waves generated from it are diffuse and are dispersed over a very wide angle. This means that loudspeaker positioning is far less critical than with conventional loudspeakers. Additionally, just like the acoustic musical instrument, Amina loudspeakers have excellent room filling abilities.

Amina loudspeakers are planar devices and this feature is further enhanced when flush mounted into your wall or ceiling. Being planar (or flat) means that the audio's arrival time to the listener is the same for all frequencies, i.e. there is very little phase distortion. Therefore Amina loudspeakers (and other planar devices such as electrostatic loudspeakers) can reproduce subtle nuances on a recording with incredible accuracy.

In addition to the above characteristics, the radiating surface of an Amina speaker is very stiff and undergoes very small amounts of movement in order to generate high sound pressure levels. This means that the loudspeakers are inherently "fast" making them highly articulate loudspeakers.


# Setup tips

## Speaker Orientation

Amina loudspeakers can be installed either in portrait or landscape orientations. Typically the spacing between wall joists will dictate portrait orientation and Amina have optimised the dispersion characteristics for this setup. Therefore when installing into walls Amina suggest portrait orientation for best sound quality.

For non-critical listening in ceiling installations the orientation of the speaker is not crucial.

For critical listening in ceilings, e.g. a 5.1 surround system, ensure that the orientation of all loudspeakers are the same relative to the main listening position and position the top of the speaker closer to the wall boundary.



## Boundary Loading

It is possible to increase the low frequency output of Amina loudspeakers by positioning them close (50mm - 150mm) to the corners of a room. This can be useful when no additional subwoofer (e.g. ALF80 or ALF120) is used.

## System Requirements

From a system compatibility point of view your speaker (and it's accompanying APU protection unit) can be treated like any conventional low impedance (4-8 ohm) loudspeaker. Amina recommends you use a good quality amplifier so as to avoid driving them with high levels of distortion, which at best, will provide poor sound quality and at worst may permanently damage the loudspeaker. Amina also recommend you connect your loudspeakers to your amplifier with at least 16AWG OFC (oxygen free) cable (14AWG for long runs) to avoid any chance of reduced efficiency and restricted audio bandwidth.

For 2.1, 5.1 and 7.1 systems always use the amplifier's crossover settings to divert frequencies below 100Hz to your subwoofer. This will improve the dynamic range and power handling of the system. (APU devices should still be used).

**IMPORTANT:** Amina loudspeakers are highly revealing of any shortcomings in the source or amplifier. Please be aware that some low cost zone amplifiers will produce high amounts of distortion well within their operating range and this will be ruthlessly revealed by Amina loudspeakers.

## Sound Transmission

As with any speaker designed to be fixed to a structure within a wall or ceiling, careful consideration should be given to sound transmission into adjacent rooms or properties. We recommend specialist advice is taken if sound transmission into adjacent rooms needs to be minimised. Please talk to the Amina technical team for advice on reducing sound transmission as a starting point.

## 100/70V Option

For multi-speaker commercial installations, please contact Amina for their range of loudspeakers supplied with 100V or 70V line transformers fitted.

# Installation

**IMPORTANT: Read this section carefully before attempting to install an Amina Edge loudspeaker.**

To avoid any possible damage to Amina invisible loudspeakers they must be mounted and connected using the correct accessories, supplied by Amina. The tables to follow list these accessories.

## Mounting accessories

Identify the construction type of the wall/ceiling where the loudspeakers are to be installed and ensure you have the correct fixing accessories to hand before installing your loudspeakers.

Full installation instructions are included with each type of mounting accessory.

Type	Application	Image
<b>BackboxCV345</b> For cavity walls and ceilings	Used to install Edge loudspeakers in cavity walls and ceilings to reduce airborne sound generation from the rear of the speaker and create optimum acoustic cavity.	
<b>Firehood 345</b> For fire-rated cavity walls	A 60 minute fire rated overjacket to use with the BackboxCV, which maintains 1 hour fire-retardancy where necessary and additionally reduces airborne sound generation from the rear of the speaker.	
<b>Basic fixing block kit</b> For cavity walls	Used to install Edge loudspeakers in cavity walls and ceilings, when BackboxCV cannot be used.	
<b>Shims</b>	Various thicknesses available to align the speaker with the front of non-standard plasterboard structures or for retrofit installations.	

Refer to the Installation guide supplied with the above mounting accessories for detailed fitting instructions of the accessory together with how the loudspeaker is used within it.

# Installation

## Speaker protectors

Amina APU series speaker protectors are specifically designed to work with Amina invisible loudspeakers. They provide essential safe operating functions and include protection elements that constantly monitor the power fed to the speaker keeping it within safe limits should the need arise.


An Amina speaker protector should be wired in-line with each Amina speaker, preferably in an accessible place, allowing this device to be replaced as necessary.

There are three types of protector.

Type	Application	Image
<b>APU-RS8i</b>	Flexible 8 channel crossover and protection unit in a 1U case for optional rack mounting. Provides protection for installations of up to 8 Amina loudspeakers of any type.	
<b>APU-RS16i</b>	16 channel crossover and protection unit in a single 1U case. Provides protection for up to 16 Amina loudspeakers of any type.	
<b>APUi</b>	Single channel crossover and protection for wiring in-line with each Amina speaker.  APUi crossovers are available in different versions and must be ordered to match the speaker being installed.	



# Installation

## Correct fixing method for BackboxCV



### IMPORTANT:

The BackBoxCV **must** be fixed to the plasterboard only. **Never** attach directly to the stud work or near supporting structure as shown in the images below.




# Installation

## Locate joist work

When you have chosen your speaker locations, before cutting a hole in the plasterboard it is important that you locate the position of the wall studs. Ensure the spacing between them is at least 5mm greater than the width of your Amina Edge speaker for a portrait orientated speaker.


If necessary cut an inspection hole in the plasterboard, use a tape measure inserted through the hole to accurately locate the edges of studs.



# Installation


## Using the Cutout Template for pre-install of BackboxCV

Staple to plasterboard/drywall to act as a template.



## Using the Cutout Template

1. Ascertain joist position behind plasterboard/ drywall.
2. Ensure cut out dimensions fit between the joists.
3. Use a knife to cut around the outside of the template.



# Installation

## Installing the BackboxCV345

Create 455 x 350 mm (17 7/8" x 13 3/4") aperture.


Using a sharp knife or pad saw, cut an aperture in your plasterboard wall or ceiling. Ensure the aperture is created between supporting joists or stud work.

We strongly advise that joists are not cut to make space for the backbox. Any activity of this sort may well influence the structural integrity of your property.



### IMPORTANT:

Double check the size of the aperture, as this is important further on into the installation process.



---

# Installation

## Shims


Once the hole is cut for the BackboxCV345 it is important to identify the construction of the wall and its thickness.

You may need to fix shims to the speaker frame or to the BackboxCV345 to correctly align the speaker.

The thickness of the shims required is shown in the alignment guide to follow and will depend on the construction of the wall and the thickness of plaster skim (if any).

## Fixing shims to the speaker

Some installations will require shims fixed to the speaker mounting face to compensate for the thickness of plaster skim. This arrangement is shown below.



## Fixing shims to the BackboxCV

Some installations will require shims fixed to the BackboxCV345 mounting face to compensate for thinner drywall or plasterboard. This arrangement is shown below.



# Alignment and preparation

## Drywall / Dry line

*For new drywall walls / ceilings*

### Alignment required for plastering

The diagram shows an Edge speaker fitted into a BackboxCV345 in a new drywall construction (not skimmed).

When correctly installed, the outer edge of the speaker panel will align with the drywall surface around the speaker and the raised centre section of the speaker panel will sit 0.8mm in front of the drywall.



### Shim sizes

#### Standard 12.5mm (1/2") drywall


No shims are required for installation in 12.5mm drywall. For other drywall thicknesses, shims will be necessary.

#### Thicker drywall

For thicker drywall, subtract 12.5mm from the thickness of the drywall to determine the shim size. Fix the shims to the mounting face of the speaker.

#### Thinner drywall

For thinner drywall, subtract the drywall thickness from 12.5mm to determine the shim size. Fix the shims to the mounting face of the BackboxCV345.



# Alignment and preparation

## Full wet skim coat


*For new plaster plasterboard walls / ceilings that received a full skim of plaster*

### Alignment required for plastering

For these installations, cut the hole for the speaker, and fit the BackboxCV345, but not the Edge speaker.

Plaster the wall up to the edge of the hole and allow the wall to dry.

When the wall is dry, refer to the alignment diagram on the next page for retro-fitting an Edge speaker into the plastered wall.



Plasterboard



Plaster

# Alignment and preparation

## Retrofit / pre-skimmed plasterboard

*For walls / ceilings that have already been plastered.*

### Alignment required for plastering

The diagram shows an Edge speaker fitted into a BackboxCV345 in a pre-skimmed wall constructed of plasterboard.

When correctly installed, the outer edge of the speaker panel will align with the plaster surface around the speaker and the raised centre section of the speaker panel will sit 0.8mm above the plaster surface.

To achieve this alignment, shims of the correct size are required when fitting an Edge speaker into a BackboxCV345.




### Shim sizes

Shims will be required to space the speaker out to meet the face of the plastered wall.

To determine the exact size of shim required, measure the thickness of the wall including plaster and subtract 12.5mm.

For example, if the wall thickness measures 14.5mm, the shim thickness required will be 2mm.

The shims are fixed to the mounting face of the speaker (see page 16).



## Testing the speakers

**Important: Always test the speaker before plastering it in and again once plaster is dry.**

**The following procedure is required as a minimum.**

### CAUTION:

*The speaker is highly efficient and will generate very high sound pressure levels with minimal power input. Take care to protect your ears when testing.*

- Using a multimeter and without the APU protection device connected, check the nominal impedance (DC resistance) of the speaker at the amplifier end of the speaker cable. Allow for approx. +10% for cable resistance. The impedance should coincide with the values on the respective loudspeaker datasheets. If it measures significantly different, check for breaks or shorts in the cable.
- Amina recommends a tone sweep be used at a moderate volume level (0.5 Vrms). Such a test will quickly highlight any buzzes or rattles that could be caused by loose screws, cables touching the speaker or loose elements/studs within the wall itself.
- If the plasterboard is not securely fastened to the joists this could also create a buzz or a rattle. Apply more screws if necessary - particularly around the speaker location.
- Ensure that the speaker cable is not touching any part of the speaker (or backbox) as this can lead to buzzes and rattles. To avoid this it is advised to lay the cable behind mineral wool, recycled cotton or other wadding.
- If metal studs are used, ensure the crossover point of the studs are secured together. This can be achieved by applying drywall screws through the wall surface and through the metal joists. If they are not secure this may well lead to audible vibrations and rattles.
- Play music to check for buzzes and rattles during transient peaks: if these are apparent, check the above points again. The overall speaker performance must be clean and distortion free.
- Always connect the APU when testing, except when measuring impedance.
- Perform these tests again after the plaster is fully dry (This could take some days).
- The speaker face, when tapped with fingers, will sound more hollow than the surrounding areas of plasterboard. If there is little or no difference between these two sounds then there is a problem with the installation that will compromise the speaker performance. Check carefully that the raised surface of the speaker panel has not been plastered in error.

Amina have a lot more information available from its technical help desk for those wishing to measure frequency response curves at different stages of the installation.

Please contact +44 (0) 1480 354390 for assistance.

# Finishing

## Filling the perimeter

Once the speaker is fixed into place, the gap must be filled with plaster to bond the edge of the panel to the edge of the plasterboard.

Wipe away filler from the panel surface (both the outer perimeter and raised sections).

Use a low shrinkage repair plaster such as British Gypson Easi-Fill® or other joint compound.

This will prevent cracking around the border.



Allow this to dry fully before continuing with the installation.




Speaker panel



Plaster to fill the edge


fill the gap between the speaker panel and the wall



## Taping the joints

Using 50mm (2") plaster jointing scrim tape, tape across the perimeter of the tape across the perimeter of the speaker frame as shown.

Paper tape can also be used. Use usual methods to apply paper tape (wetted if necessary and set into wet joint compound).




# Finishing

## Feathering the panel edge

Feather in plaster to the edge of the raised section.

-  Speaker panel
-  Plaster to fill the edge
-  Feathered surface filler skim
-  Original plaster
-  Plasterboard



## Cutaway view

This cutaway view shows a section through the finished skim in the area shown.

## Finishing

To finish the installation, a very light coat of surface filler (less than 0.5mm) may be used to blend the panel appearance with the surrounding plaster. Filler can be sanded/wiped smooth to achieve correct texture, care should be taken not to sand any exposed paper panel surface.'

---

## Decorating

Allow your plasterwork to dry completely. Test the speaker again. You can then paint the surface or hang wallpaper in the usual manner.

Amina Invisible speakers have been optimised for three coats of emulsion once plastered. Additional coats will cause very small reductions in the maximum sound pressure levels achievable.

Completed and fully dried plaster surfaces should be finished with permeable coatings / materials to allow moisture in that coating or the adhesives used to apply those materials, to dry into the environment quickly.

Oil based coatings and other non-permeable surfaces will trap moisture in the plaster surface for many days and even weeks. This has the potential to work its way back to the Amina loudspeakers exposing them to an unacceptably damp environment for an extended period.

The use of impermeable coatings and materials should be considered carefully and with caution. Bare plaster surfaces must be pre-treated with a primer / sealing coat that is permeable during its drying process. The entire surface must then be fully dry (this may take some weeks) before applying the impermeable coating or material.

## Maintenance and cleaning

Once your speaker is plastered into your wall or ceiling, it requires no physical maintenance. Your wall or ceiling can be cleaned with products appropriate to the finish finally applied to the plaster surface.

The wall or ceiling can be painted or redecorated any number of times, but please be aware that sound output will reduce slightly with each coat. Extreme care should be taken when removing wallpaper type coverings to ensure the panel surface is not damaged. If damage to the plaster work occurs, use repair plaster to restore the plaster surface prior to re-decorating. Amina Technologies Ltd recommends British Gypsum Easi-fill® repair plaster.

Avoid pushing the wall or ceiling surface immediately in front of the speaker. Excessive excursion, whilst unlikely to damage the speaker, will undoubtedly cause the plaster to crack around its perimeter.

---

# Accessories

## Subwoofers


### ALF80

150W passive subwoofer with unique adjustable port design allowing the product to be installed within joinery, behind kick boards or within ceilings or other voids. Highly discrete, powerful and deep bass response is achieved with only a small opening for the port required within the room.



### ALF120

Amina have developed an astonishing subwoofer technology dubbed 'distributed transmission line' (DTL), which allows the design of a subwoofer thin enough to be built into a stud wall, venting through a simple slot in the skirting board, to create an impressively low 27Hz audio output at 111dB loudness using only 50W of power.



---

# Troubleshooting

Thorough testing of the loudspeakers should be carried out both prior to and after plastering to avoid time consuming repairs or modifications at a later stage. Should you encounter any problems at either of the test stages the following guide is designed to help determine possible problem areas.

## Advice for testing

- When testing always use a basic sound system (amp, source, loudspeakers) to eliminate the possibility of faults with other, more sophisticated components, such as control systems.
- Test at low and medium volumes and be careful not to exceed the specific speaker model's recommended power. Using tone sweeps or music as test material, listen for distortion, buzzing or rattles at appropriate levels. Using test discs or music, confirm that all channels are in-phase.
- Ideally professional test equipment should be used to record a full frequency response of the loudspeaker before and after plastering.

## No or low sound output

- Check continuity of all cables.
  - Check that all cables and connections are made correctly, are intact and that all channels are correctly phased (+ to + and - to - from amp to speaker).
  - Using an impedance meter, check the nominal impedance of the speaker (APU must not be connected) both at the loudspeaker and the amp end of the cable. Do these measurements match each other? (Allowing for the small impedance increase of less than 1 ohm along the wire length) Do they match the stated nominal impedance on the loudspeakers specification label? If the nominal impedance, measured at the loudspeaker is dramatically different to the product's stated impedance, a speaker driver may be open circuited or short circuited. If so, the product may need to be returned to Amina for repair or replacement.
  - If the nominal impedance at the end of the cable is very different to the impedance at the speaker, check your cables. Cuts or nicks in the cable along its length can dramatically increase impedance or create a short circuit, dramatically lowering the impedance.
-

---

# Troubleshooting

## Distortion, buzzing or rattles at modest volumes

- Try to identify the location of the buzz or rattle. It may be caused by a loose screw or other mechanical object. Check the wall or ceiling and speaker assembly and ensure screws and fixings are tight.
- If the rattle persists, remove the speaker from the wall and check your wiring to the product. Ensure that wires, with the speaker in the final location, are not resting against the speaker or backbox (if used), causing vibrations.
- With no audio signal applied, lightly push the speaker face in and out at its centre. Listen carefully for rubbing on the driver, which may sound like scratching. This may indicate the speaker has been over driven and subsequently damaged. The speaker will need to be sent to Amina for repair or replacement.

## Very low output after speaker passes electrical tests

- With no audio signal applied, lightly push the panel in and out at its center. Listen carefully for rubbing voice coils on the driver, which may sound like scratching. This may indicate the speaker has been over driven and subsequently damaged. The speaker will need to be sent to Amina for repair.

## Distortion at higher volume levels

- Diffuse source panel loudspeakers of this type have an extremely fast response, articulating the signal from your audio system very accurately. Take your system back to the bare minimum (amplifier, source and loudspeakers) to eliminate distortions introduced by other components.
  - When using your amplifier at maximum power levels, or if the input of your amplifier is being overloaded, the signal level may be 'clipping'. With some conventional loudspeakers this may not be evident, but with a diffuse source panel speaker you are much more likely to hear the distortion. Consider adjusting or upgrading your system.
-

# Specifications

## Amina Edge series - Plaster up to products

Model number	Edge5	Edge7
Dimensions	450mm x 345mm x 34mm (17 <sup>3</sup> / <sub>4</sub> " x 13 <sup>5</sup> / <sub>8</sub> " x 1 <sup>5</sup> / <sub>16</sub> " )	
Weight	1.70kg (3lbs 12oz)	1.80kg (3lbs 15oz)
Nominal impedance	8Ω	4Ω
Frequency response	65Hz to 20kHz	40Hz to 20kHz
Sensitivity (@ 1m/2.83Vrms)	90dB	93dB
In-line protection unit (single channel)	APUi50	APUi70
In-line protection unit (multi-channel)	APU-RS8i/ APU-RS16i	
Fixing requirement	Amina BackboxCV345 / Basic fixing kit	
Power handling (continuous)	50W	75W
Power handling (peak)	100W	150W
Operating temperature range	16°C - 40°C	
Manufacturer warranty	10 years (residential systems), 5 years (commercial systems)	

---

## Warranty information

### Limited Warranty:

Amina loudspeakers are designed to operate reliably for many years. Correctly installed in accordance with these instructions, Amina warrants the loudspeakers against defective materials and manufacturing workmanship for a period of ten years in residential and five years in commercial applications.

At the end of the speaker's useful life and in compliance with the European directive on waste electrical and electronic equipment (WEEE), this product is to be returned to your supplier, or directly to Amina for recycling. If you have any questions please contact Amina Technologies Ltd.

\* Please refer to our full warranty statement for details, available **on our website, or alternatively contact us via email.**



**Important Note:** This product does not comply to European Construction Products Directive EN 54-24 and therefore must not be used in voice evacuation systems located within the European Union.

## Copyright information

This document is Copyright of Amina Technologies Ltd, 2016

Easi-Fill is a registered trademark of British Gypsum Ltd

Amina is a registered trademark of Amina Technologies Ltd

## Contact information

### Amina Technologies Ltd

Cirrus House, Glebe Road, Huntingdon

Cambridge, PE29 7DL, UK

T: +44 (0) 1480 354390

E: [inspired@amina.co.uk](mailto:inspired@amina.co.uk)

W: [www.amina.co.uk](http://www.amina.co.uk)

### North America

Direct 503.256.2600

Toll free 1-800.666.6316

Fax 503.256.5966

E: [salesna@amina.co.uk](mailto:salesna@amina.co.uk)

---



---

*amina*®

---

THE INVISIBLE SPEAKER CO.

Amina Technologies Ltd  
Cirrus House, Glebe Road  
Huntingdon, Cambs, PE29 7DL England  
T: +44 1480 354390  
W: [www.amina.co.uk](http://www.amina.co.uk) / E: [inspired@amina.co.uk](mailto:inspired@amina.co.uk)  
Copyright 2016

Edge with BackboxCV V1.6

---